




IMMERSION HEATERS

SPECIFICATION: Porcelain core removable pattern elements with Nichrome coils in solid drawn steel tubes. Terminal covers tapped for conduit—Weathertight (W.T.) Screw or flange fixing. Surface rating 10W/□". B.S.S. 799/1953 recommendation 8W/□". For C.T.F. fuels and liquid tar see Price List.

CI Series

(1½" o/d TUBE—W.T. head—1½" B.S.P.)



CI — C3

List No.	Immersed length		Wattage	List No.	Immersed length	
	10 W/□"	8 W/□"			10 W/□"	8 W/□"
CI05/	12"	/15"	500 W	CF105/	12"	/15"
CI10/	22"	/27"	1 KW	CF110/	22"	/27"
CI15/	33"	/40"	1½ KW	CF115/	33"	/40"
CI20/	44"	/54"	2 KW	CF120/	44"	/54"
CI25/	55"	/66"	2½ KW	CF125/	55"	/66"
CI30/	66"	/80"	3 KW	CF130/	66"	/80"
CI35/	75"	/92"	3½ KW	CF135/	75"	/92"
CI40/	86"	/108"	4 KW	CF140/	86"	/108"

Distance across corners = 3¼"
Distance across flats = 2¾"

Height of head = 3¼"

Flange 5¼" o/d 4-½" bolts 3½" PCD
⅜" thk.

CFI Series

(1½" o/d—W.T.—Flanged)

C3 Series

2" o/d TUBE—W.T. head—2" B.S.P.)

List No.	Immersed length		Wattage	List No.	Immersed length	
	10 W/□"	8 W/□"			10 W/□"	8 W/□"
C310/	16"	/20"	1 KW	CF310/	16"	/20"
C315/	24"	/30"	1½ KW	CF315/	24"	/30"
C320/	32"	/40"	2 KW	CF320/	32"	/40"
C325/	40"	/50"	2½ KW	CF325/	40"	/50"
C330/	48"	/60"	3 KW	CF330/	48"	/60"
C335/	56"	/70"	3½ KW	CF335/	56"	/70"
C340/	64"	/80"	4 KW	CF340/	64"	/80"
C350/	80"	/100"	5 KW	CF350/	80"	/100"
C360/	96"	/120"	6 KW	CF360/	96"	/120"

Distance across corners = 3¼"
Distance across flats = 3⅞"

Height of head = 3¼"

Flange 6½" o/d, 4-⅝" bolts 5" PCD
⅝" thk.



CFI — CF3

DUNCAN LOW LIMITED • • GLASGOW N.W.

Dunlow Spares and replacements from :

A.K. WAUGH

Division of Cormac Engineering Ltd.

**274-278 Whitehill Street,
Dennistoun, Glasgow G31 3EL**

T : +44 141 440 5775

E : sales@akwaugh.com

W : www.akwaugh.com